



TorcStark KLCD Series Low Clearance Wrench Overview

- *70MPa max working pressure.
- *Torque repeatability up to 3%.
- *11 models with the ranges from 237-85000Nm.
- *360×180 degree swivel joint, no space limitation.
- *Integral design, high strength and high toughness.
- *Al-Ti alloy material.
- *Working head and supporting point are coaxial, perfect structure, long service life.
- *One power head can match different ratchet links.

Features

- Model: KLCD
- Tool type: Low profile
- Torque range: 237-85000Nm
- A/F range: 36mm-180mm
- Brand: TorcStark
- Origin: Made in China
- Warranty: One year
- Packing: Double packing, Aluminium plastic box + wooden box

| Model | 3KLCD | 4KLCD | 8KLCD | | | | | | | | Torque (Nm) | 345 3446 | 546 5458 | 1055 10550 | 1848 18484 | 2481 24814 | 2909 29089 | 4231 42311 | 5209 52088 | 6057 60566 | 8415 84150 |
|--------------------------|-------|-------|--------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|-------------|-------------|-------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| A/F(mm) | 36-60 | 46-80 | 70-105 | | | | | | | | 80-115 | 85-120 | 90-130 | 95-145 | 120-145 | 130-155 | 135-180 | | | | |
| Power head weight (kg) | 0.8 | 1.9 | 4.2 | 14KLCD | 18KLCD | 20KLCD | 30KLCD | 40KLCD | 45KLCD | 60KLCD | 6.8 | 8.1 | 10.5 | 12.7 | 15.2 | 16.3 | 23 | | | | |
| Ratchet link weight (kg) | 1.7 | 3.6 | 7.6 | | | | | | | | 12.2 | 19.3 | 22.3 | 32.3 | 47.5 | 58.7 | 75 | | | | |
| L(mm) | 218 | 266 | 324 | | | | | | | | 382 | 404 | 427 | 479 | 479 | 486 | 514 | | | | |
| H1(mm) | 118 | 139 | 171 | 205 | 229 | 240 | 268 | 285 | 311 | 336 | | | | | | | | | | | |
| H2(mm) | 156 | 167 | 198 | 231 | 255 | 265 | 289 | 302 | 352 | 375 | | | | | | | | | | | |
| W1(mm) | 32 | 42 | 53 | 64 | 68 | 70 | 85 | 98 | 105 | 117 | | | | | | | | | | | |
| W2(mm) | 50 | 66 | 83 | 99 | 105 | 110 | 132 | 148 | 160 | 177 | | | | | | | | | | | |